

model F-20



High Temp Dish & Tray Warewasher

**Fully automatic program with wash phase at 150F.
and final rinse phase at 185F.**

Capacity: 24 racks per hour

**Sanitary labyrinth door eliminates the need for gasket
Integrated rinse-additive pump for sparkling results
Integrated automatic detergent pump for consistent results
Ergonomically designed for ease of loading racks**

CONSTRUCTION FEATURES

- Body, external housing, wash tank, and all chassis components in brushed stainless steel AISI 304 18/10
- Reduced operating noise of 58 DbA due to utilization of double-wall insulated panels providing thermic and acoustic insulation
- Ergonomically designed for ease of loading / unloading racks which is preformed at waist level
- Very practical for churches, schools, retirement homes, and for washing of trays to a maximum size of 15" x 21"
- Built with fully enclosed cabinet base used as storage area
- Upper and lower wash and rinse jets on revolving arms constructed of fiberglass; easy to remove and clean without the need for tools
- Integrated 18/10 stainless steel booster
- Safety micro-switch on the door to interrupt wash pump action
- Independently-operated heating elements alternating between booster and wash tank for a reduced electrical consumption
- Individual analog thermometer gauges for both wash and rinse temperatures
- Automatic water level regulation of wash tank
- Adjustable variable speed peristaltic pumps for detergent & rinse-additive
- Standard equipment includes insulated, stainless steel top & side panels
- Wash tank protected with double full filters with additional filter for wash pump protection
- Door opening with overall clearance of 15 in. (38cm)
- Overall dimensions: Height: 54.5 in. (138 cm) Width 25.75 in. (66 cm) Depth: 24.0 in. (61 cm)

JET TECH SYSTEMS CORP.

TEL: (514) 737-9701
FAX: (514) 342-3854
TOLL-FREE: (888) 275-4538
www.jet-tech.com
info@jet-tech.com



Wide capacity for trays
(Basket shown not included)

TECHNICAL FEATURES

- Rack capacity: 19.75" x 19.75" (50 cm x 50 cm)
- 1 open combination rack and 1 peg rack are supplied)
- Complete cycle: 160 seconds (140 sec. wash & 20 sec. rinse)
- Wash temperature: 150F
- Rinse temperature: 185F
- Power supply: Single phase 208-240V. 60hz 33A
- Motor pump: 1.2 HP with thermal overload protection
- Wash tank capacity: 7.5 U.S. Gallons (28 liters)
- Booster capacity: 2.7 U.S. Gallons (10.2 liters)
- Wash tank element: 4 KW
- Booster element: 6 KW
- Maximum Power rating: 7.1 KW
- Water consumption per cycle: 0.79 U.S. Gallon (3.0 liters)
- Working pressure: 25 p.s.i. (dynamic)
- Water inlet connection: 3/4" NPT male
- Shipping weight: 198 Lbs (90 Kg.)
- Drain connection: 1.5" I.D. (hose not supplied)
- OPTION: Installation kit "G" (recommended)

