

Computer

Summary

Computer

Processor	Intel(R) Pentium(R) 4 CPU 2.20GHz
Memory	1024MB (367MB used)
Operating System	Ubuntu 14.04.1 LTS
User Name	inspiron (INSPIRON)
Date/Time	Sun 21 Sep 2014 04:28:50 PM EDT

Display

Resolution	1024x768 pixels
OpenGL Renderer	Unknown
X11 Vendor	The X.Org Foundation

Multimedia

Audio Adapter	ICH4 - Intel 82801DB-ICH4
---------------	---------------------------

Input Devices

Lid Switch
Power Button
Sleep Button
AT Translated Set 2 keyboard
SynPS/2 Synaptics TouchPad
Video Bus

Printers

No printers found

SCSI Disks

SONY CDRW/DVD CRX830E
ATA Hitachi HTS54121

Operating System

Version

Kernel	Linux 3.13.0-35-generic (i686)
Compiled	#62-Ubuntu SMP Fri Aug 15 01:58:01 UTC 2014
C Library	Unknown
Default C Compiler	Unknown
Distribution	Ubuntu 14.04.1 LTS

Current Session

Computer Name inspiron-Inspiron-1100
 User Name inspiron (INSPIRON)
 Home Directory /home/inspiron
 Desktop Environment LXDE (Lubuntu)

Misc

Uptime 17 minutes
 Load Average 0.48, 0.48, 0.39

Kernel Modules**Loaded Modules**

ctr CTR Counter block mode
 ccm Counter with CBC MAC
 arc4 ARC4 Cipher Algorithm
 ath5k Support for 5xxx series of Atheros 802.11 wireless LAN cards.
 ath Shared library for Atheros wireless LAN cards.
 mac80211 IEEE 802.11 subsystem
 cfg80211 wireless configuration support
 gpio_ich GPIO interface for Intel ICH series
 snd_intel8x0 Intel 82801AA,82901AB,i810,i820,i830,i840,i845,MX440; SiS 7012; Ali
 5455
 snd_ac97_codec Universal interface for Audio Codec '97
 ac97_bus
 snd_pcm Midlevel PCM code for ALSA.
 snd_page_alloc Memory allocator for ALSA system.
 snd_seq_midi Advanced Linux Sound Architecture sequencer MIDI synth.
 snd_seq_midi_event MIDI byte <-> sequencer event coder
 snd_rawmidi Midlevel RawMidi code for ALSA.
 dell_laptop Dell laptop driver
 snd_seq Advanced Linux Sound Architecture sequencer.
 dcdbas Dell Systems Management Base Driver (version 5.6.0-3.2)
 pcmcia PCMCIA Driver Services
 bnep Bluetooth BNEP ver 1.3
 rfcomm Bluetooth RFCOMM ver 1.11
 bluetooth Bluetooth Core ver 2.17
 snd_seq_device ALSA sequencer device management
 snd_timer ALSA timer interface
 yenta_socket
 pcmcia_rsrc

i915	Intel Graphics
snd	Advanced Linux Sound Architecture driver for soundcards.
pcmcia_core	Linux Kernel Card Services
drm_kms_helper	DRM KMS helper
joydev	Joystick device interfaces
lpc_ich	LPC interface for Intel ICH
serio_raw	Raw serio driver
shpchp	Standard Hot Plug PCI Controller Driver
soundcore	Core sound module
drm	DRM shared core routines
i2c_algo_bit	I2C-Bus bit-banging algorithm
mac_hid	
parport_pc	PC-style parallel port driver
ppdev	
video	ACPI Video Driver
lp	
parport	
psmouse	PS/2 mouse driver
b44	Broadcom 44xx/47xx 10/100 PCI ethernet driver
ssb	Sonics Silicon Backplane driver
mii	MII hardware support library

Boots

Boots

Sun Sep 21 16:11 3..13.0-35-generi|-
Sun Sep 21 15:55 3..13.0-35-generi|-
Sun Sep 21 15:53 3..13.0-35-generi|-
Sun Sep 21 15:37 3..13.0-35-generi|-
Sun Sep 21 15:09 3..13.0-32-generi|-
Sun Sep 21 15:08 3..13.0-32-generi|-
Sun Sep 21 15:06 3..13.0-32-generi|-
Sun Sep 21 14:59 3..13.0-32-generi|-
Sun Sep 21 14:56 3..13.0-32-generi|-

Languages

Available Languages

en_AG English language locale for Antigua and Barbuda
en_AG.utf8 English language locale for Antigua and Barbuda

en_AU.utf8 English locale for Australia
 en_BW.utf8 English locale for Botswana
 en_CA.utf8 English locale for Canada
 en_DK.utf8 English locale for Denmark
 en_GB.utf8 English locale for Britain
 en_HK.utf8 English locale for Hong Kong
 en_IE.utf8 English locale for Ireland
 en_IN English language locale for India
 en_IN.utf8 English language locale for India
 en_NG English locale for Nigeria
 en_NG.utf8 English locale for Nigeria
 en_NZ.utf8 English locale for New Zealand
 en_PH.utf8 English language locale for Philippines
 en_SG.utf8 English language locale for Singapore
 en_US.utf8 English locale for the USA
 en_ZA.utf8 English locale for South Africa
 en_ZM English locale for Zambia
 en_ZM.utf8 English locale for Zambia
 en_ZW.utf8 English locale for Zimbabwe

Filesystems

Mounted File Systems

/dev/sda1 /	8.36 % (83.0 GiB of 90.6 GiB)
none /sys/fs/cgroup	0.00 % (4.0 KiB of 4.0 KiB)
udev /dev	0.00 % (491.0 MiB of 491.0 MiB)
tmpfs /run	0.93 % (99.1 MiB of 100.1 MiB)
none /run/lock	0.00 % (5.0 MiB of 5.0 MiB)
none /run/shm	0.00 % (500.4 MiB of 500.4 MiB)
none /run/user	0.02 % (100.0 MiB of 100.0 MiB)

Display

Display

Resolution	1024x768 pixels
Vendor	The X.Org Foundation
Version	1.15.1

Monitors

Monitor 0	1024x768 pixels
-----------	-----------------

Extensions

BIG-REQUESTS
Composite
DAMAGE
DOUBLE-BUFFER
DPMS
DRI2
DRI3
GLX
Generic Event Extension
MIT-SCREEN-SAVER
MIT-SHM
Present
RANDR
RECORD
RENDER
SECURITY
SGI-GLX
SHAPE
SYNC
X-Resource
XC-MISC
XFIXES
XFree86-DGA
XFree86-VidModeExtension
XINERAMA
XInputExtension
XKEYBOARD
XTEST
XVideo

OpenGL

Vendor	Unknown
Renderer	Unknown
Version	Unknown
Direct Rendering	No

Environment Variables

Environment Variables

USER	inspiron
LANGUAGE	en_US

```
UPSTART_INSTANCE
XDG_SEAT                seat0
TEXTDOMAIN              im-config
SSH_AGENT_PID           1299
SESSION                 Lubuntu
HOME                    /home/inspiron
QT4_IM_MODULE           xim
DESKTOP_SESSION         Lubuntu
XDG_SEAT_PATH           /org/freedesktop/DisplayManager/Seat0
INSTANCE
DBUS_SESSION_BUS_ADDRESS unix:abstract=/tmp/dbus-TfI26qG88t
MANDATORY_PATH          /usr/share/gconf/Lubuntu.mandatory.path
IM_CONFIG_PHASE         1
SESSIONTYPE             lxsession
UPSTART_JOB             lxsession
LOGNAME                 inspiron
GTK_IM_MODULE           xim
DEFAULTS_PATH           /usr/share/gconf/Lubuntu.default.path
XDG_SESSION_ID          c2
PATH                    /usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr
                        /games:/usr/local/games
GDM_LANG                en_US
SELINUX_INIT            YES
XDG_SESSION_PATH        /org/freedesktop/DisplayManager/Session0
XDG_RUNTIME_DIR         /run/user/1000
DISPLAY                 :0
LANG                    en_US.UTF-8
XAUTHORITY              /home/inspiron/.Xauthority
XMODIFIERS              @im=ibus
XDG_GREETER_DATA_DIR    /var/lib/lightdm-data/inspiron
SSH_AUTH_SOCK           /tmp/ssh-0muM1hgBnqSY/agent.1295
SSH_AGENT_LAUNCHER      upstart
SHELL                   /bin/bash
GDMSESSION              Lubuntu
UPSTART_EVENTS          started xsession
TEXTDOMAINDIR           /usr/share/locale/
UPSTART_SESSION         unix:abstract=/com/ubuntu/upstart-session/1000/1251
XDG_VTNR                7
QT_IM_MODULE            xim
PWD                     /home/inspiron
```

XDG_CONFIG_DIRS	/etc/xdg/lubuntu:/etc/xdg/xdg-Lubuntu:/usr/share/upstart /xdg:/etc/xdg
XDG_DATA_DIRS	/etc/xdg/lubuntu:/usr/local/share:/usr/share:/usr/share /gdm:/var/lib/menu-xdg:/usr/share/Lubuntu:/usr/local/share /:/usr/share/
CLUTTER_IM_MODULE	xim
JOB	dbus
XDG_CURRENT_DESKTOP	LXDE
_LXSESSION_PID	1328
XDG_CONFIG_HOME	/home/inspiron/.config
XDG_MENU_PREFIX	lxde-
SAL_USE_VCLPLUGIN	gtk

Users

Users

root	root
daemon	daemon
bin	bin
sys	sys
sync	sync
games	games
man	man
lp	lp
mail	mail
news	news
uucp	uucp
proxy	proxy
www-data	www-data
backup	backup
list	Mailing List Manager
irc	ircd
gnats	Gnats Bug-Reporting System (admin)
nobody	nobody
libuid	
syslog	
messagebus	
usbmux	usbmux daemon
dnsmasq	dnsmasq
ntp	
whoopsie	

lightdm	Light Display Manager
inspiron	INSPIRON

Devices

Processor

Processor

Name	Intel(R) Pentium(R) 4 CPU 2.20GHz
Family, model, stepping	15, 2, 9 (Pentium 4)
Vendor	Intel

Configuration

Cache Size	512kb
Frequency	2192.78MHz
BogoMIPS	4385.55
Byte Order	Little Endian

Features

FDIV Bug	no
HLT Bug	no
F00F Bug	no
Coma Bug	no
Has FPU	yes

Cache

Cache information not available

Capabilities

fpu	Floating Point Unit
vme	Virtual 86 Mode Extension
de	Debug Extensions - I/O breakpoints
pse	Page Size Extensions (4MB pages)
tsc	Time Stamp Counter and RDTSC instruction
msr	Model Specific Registers
pae	Physical Address Extensions
mce	Machine Check Architecture
cx8	CMPXCHG8 instruction
sep	Fast System Call (SYSENTER/SYSEXIT)
mtrr	Memory Type Range Registers
pge	Page Global Enable
mca	Machine Check Architecture

cmov	Conditional Move instruction
pat	Page Attribute Table
pse36	36bit Page Size Extensions
clflush	Cache Line Flush instruction
dts	Debug Store
acpi	Thermal Monitor and Software Controlled Clock
mmx	MMX technology
fxsr	FXSAVE and FXRSTOR instructions
sse	SSE instructions
sse2	SSE2 (WNI) instructions
ss	Self Snoop
ht	HyperThreading
tm	Thermal Monitor
pbe	Pending Break Enable
pebs	Precise-Event Based Sampling
bts	Branch Trace Store
cid	Context ID
xtp	Send Task Priority Messages

Memory

Memory

Total Memory	1024788 kB
Free Memory	85912 kB
Buffers	33468 kB
Cached	571568 kB
Cached Swap	0 kB
Active	506528 kB
Inactive	385848 kB
Active(anon)	283584 kB
Inactive(anon)	60900 kB
Active(file)	222944 kB
Inactive(file)	324948 kB
Unevictable	32 kB
Mlocked	32 kB
High Memory	133932 kB
Free High Memory	1764 kB
Low Memory	890856 kB
Free Low Memory	84148 kB
Virtual Memory	1038332 kB

Free Virtual Memory	1038332 kB
Dirty	312 kB
Writeback	0 kB
AnonPages	287420 kB
Mapped	112480 kB
Shmem	57088 kB
Slab	29256 kB
SReclaimable	19400 kB
SUnreclaim	9856 kB
KernelStack	2672 kB
PageTables	5260 kB
NFS_Unstable	0 kB
Bounce	0 kB
WritebackTmp	0 kB
CommitLimit	1550724 kB
Committed_AS	1859716 kB
VmallocTotal	122880 kB
VmallocUsed	8736 kB
VmallocChunk	111176 kB
HardwareCorrupted	0 kB
AnonHugePages	100352 kB
HugePages_Total	0
HugePages_Free	0
HugePages_Rsvd	0
HugePages_Surp	0
Hugepagesize	2048 kB
DirectMap4k	24568 kB
DirectMap2M	888832 kB

PCI Devices

PCI Devices

Host bridge	Intel Corporation 82845G/GL[Brookdale-G]/GE/PE DRAM Controller/Host-Hub Interface (rev 03)
VGA compatible controller	Intel Corporation 82845G/GL[Brookdale-G]/GE Chipset Integrated Graphics Device (rev 03) (prog-if 00 [VGA controller])
USB controller	Intel Corporation 82801DB/DBL/DBM (ICH4/ICH4-L/ICH4-M) USB UHCI Controller #1 (rev 02) (prog-if 00 [UHCI])
USB controller	Intel Corporation 82801DB/DBL/DBM (ICH4/ICH4-L/ICH4-M) USB UHCI Controller #2 (rev 02) (prog-if 00 [UHCI])

USB controller	Intel Corporation 82801DB/DBL/DBM (ICH4/ICH4-L/ICH4-M) USB UHCI Controller #3 (rev 02) (prog-if 00 [UHCI])
USB controller	Intel Corporation 82801DB/DBM (ICH4/ICH4-M) USB2 EHCI Controller (rev 02) (prog-if 20 [EHCI])
PCI bridge	Intel Corporation 82801 PCI Bridge (rev 82) (prog-if 00 [Normal decode])
ISA bridge	Intel Corporation 82801DB/DBL (ICH4/ICH4-L) LPC Interface Bridge (rev 02)
IDE interface	Intel Corporation 82801DB (ICH4) IDE Controller (rev 02) (prog-if 8a [Master SecP PriP])
Multimedia audio controller	Intel Corporation 82801DB/DBL/DBM (ICH4/ICH4-L/ICH4-M) AC'97 Audio Controller (rev 02)
Ethernet controller	Broadcom Corporation BCM4401 100Base-T (rev 01)
CardBus bridge	Texas Instruments PCI1510 PC card Cardbus Controller
Ethernet controller	Qualcomm Atheros AR5212/AR5213 Wireless Network Adapter (rev 01)

USB Devices

Printers

Printers

No printers found

Battery

Battery: BAT0

State	charged (load: unknown)
Capacity	6600 mAh / 6600 mAh (100.00%)
Battery Technology	rechargeable (LION)
Model Number	DELL 00
Serial Number	1

Sensors

Input Devices

Input Devices

Lid Switch
 Power Button
 Sleep Button
 AT Translated Set 2 keyboard

SynPS/2 Synaptics TouchPad
Video Bus

Storage

SCSI Disks

SONY CDRW/DVD CRX830E
ATA Hitachi HTS54121

DMI

BIOS

Date 10/18/2004
Vendor Dell Computer Corporation (www.dell.com)
Version A32

Board

Name
Vendor Dell Computer Corporation (www.dell.com)

Resources

I/O Ports

0000-001f	dma1
0020-0021	pic1
0040-0043	timer0
0050-0053	timer1
0060-0060	keyboard
0064-0064	keyboard
0070-0071	rtc0
0080-008f	dma page reg
00a0-00a1	pic2
00c0-00df	dma2
00f0-00ff	fpu
0170-0177	Intel Corporation 82801DB (ICH4) IDE Controller (rev 02) (prog-if 8a [Master SecP PriP])
0170-0177	ata_piix
01f0-01f7	Intel Corporation 82801DB (ICH4) IDE Controller (rev 02) (prog-if 8a [Master SecP PriP])
01f0-01f7	ata_piix
0376-0376	Intel Corporation 82801DB (ICH4) IDE Controller (rev 02) (prog-if 8a [Master SecP PriP])

0376-0376	ata_piix
03c0-03df	vga+
03f6-03f6	Intel Corporation 82801DB (ICH4) IDE Controller (rev 02) (prog-if 8a [Master SecP PriP])
03f6-03f6	ata_piix
04d0-04d1	pnp 00:01
07b0-07bb	pnp 00:0a
07c0-07df	pnp 00:0a
0800-087f	Intel Corporation 82801DB/DBL (ICH4/ICH4-L) LPC Interface Bridge (rev 02)
0800-0803	ACPI PM1a_EVT_BLK
0804-0805	ACPI PM1a_CNT_BLK
0808-080b	ACPI PM_TMR
0820-0820	ACPI PM2_CNT_BLK
0828-082f	GPIO interface for Intel ICH series
0828-082f	ACPI GPE0_BLK
0830-0833	iTCO_wdt
0860-087f	iTCO_wdt
0880-08bf	GPIO interface for Intel ICH series
0880-08bf	Intel Corporation 82801DB/DBL (ICH4/ICH4-L) LPC Interface Bridge (rev 02)
0880-08bf	pnp 00:02
08c0-08df	pnp 00:02
08e0-08e5	ACPI CPU throttle
0900-097f	pnp 00:07
0bb0-0bbb	pnp 00:0a
0bc0-0bdf	pnp 00:0a
0cf8-0cff	PCI conf1
0fb0-0fbb	pnp 00:0a
0fc0-0fdf	pnp 00:0a
13b0-13bb	pnp 00:0a
13c0-13df	pnp 00:0a
17b0-17bb	pnp 00:0a
17c0-17df	pnp 00:0a
1bb0-1bbb	pnp 00:0a
1bc0-1bdf	pnp 00:0a
1fb0-1fbb	pnp 00:0a
1fc0-1fdf	pnp 00:0a
23b0-23bb	pnp 00:0a
23c0-23df	pnp 00:0a
27b0-27bb	pnp 00:0a
27c0-27df	pnp 00:0a

2bb0-2bbb	pnp 00:0a
2bc0-2bdf	pnp 00:0a
2fb0-2fbb	pnp 00:0a
2fc0-2fdf	pnp 00:0a
33b0-33bb	pnp 00:0a
33c0-33df	pnp 00:0a
37b0-37bb	pnp 00:0a
37c0-37df	pnp 00:0a
3bb0-3bbb	pnp 00:0a
3bc0-3bdf	pnp 00:0a
3fb0-3fbb	pnp 00:0a
3fc0-3fdf	pnp 00:0a
43b0-43bb	pnp 00:0a
43c0-43df	pnp 00:0a
47b0-47bb	pnp 00:0a
47c0-47df	pnp 00:0a
4bb0-4bbb	pnp 00:0a
4bc0-4bdf	pnp 00:0a
4fb0-4fbb	pnp 00:0a
4fc0-4fdf	pnp 00:0a
53b0-53bb	pnp 00:0a
53c0-53df	pnp 00:0a
57b0-57bb	pnp 00:0a
57c0-57df	pnp 00:0a
5bb0-5bbb	pnp 00:0a
5bc0-5bdf	pnp 00:0a
5fb0-5fbb	pnp 00:0a
5fc0-5fdf	pnp 00:0a
63b0-63bb	pnp 00:0a
63c0-63df	pnp 00:0a
67b0-67bb	pnp 00:0a
67c0-67df	pnp 00:0a
6bb0-6bbb	pnp 00:0a
6bc0-6bdf	pnp 00:0a
6fb0-6fbb	pnp 00:0a
6fc0-6fdf	pnp 00:0a
73b0-73bb	pnp 00:0a
73c0-73df	pnp 00:0a
77b0-77bb	pnp 00:0a
77c0-77df	pnp 00:0a

7bb0-7bbb	pnp 00:0a
7bc0-7bdf	pnp 00:0a
7fb0-7fbb	pnp 00:0a
7fc0-7fdf	pnp 00:0a
83b0-83bb	pnp 00:0a
83c0-83df	pnp 00:0a
87b0-87bb	pnp 00:0a
87c0-87df	pnp 00:0a
8bb0-8bbb	pnp 00:0a
8bc0-8bdf	pnp 00:0a
8fb0-8fbb	pnp 00:0a
8fc0-8fdf	pnp 00:0a
93b0-93bb	pnp 00:0a
93c0-93df	pnp 00:0a
97b0-97bb	pnp 00:0a
97c0-97df	pnp 00:0a
9bb0-9bbb	pnp 00:0a
9bc0-9bdf	pnp 00:0a
9fb0-9fbb	pnp 00:0a
9fc0-9fdf	pnp 00:0a
a3b0-a3bb	pnp 00:0a
a3c0-a3df	pnp 00:0a
a7b0-a7bb	pnp 00:0a
a7c0-a7df	pnp 00:0a
abb0-abbb	pnp 00:0a
abc0-abdf	pnp 00:0a
afb0-afbb	pnp 00:0a
afc0-afdf	pnp 00:0a
b3b0-b3bb	pnp 00:0a
b3c0-b3df	pnp 00:0a
b7b0-b7bb	pnp 00:0a
b7c0-b7df	pnp 00:0a
bbb0-bbbb	pnp 00:0a
bbc0-bbdf	pnp 00:0a
bf20-bf3f	Intel Corporation 82801DB/DBL/DBM (ICH4/ICH4-L/ICH4-M) USB UHCI Controller #3 (rev 02) (prog-if 00 [UHCI])
bf20-bf3f	uhci_hcd
bf40-bf5f	Intel Corporation 82801DB/DBL/DBM (ICH4/ICH4-L/ICH4-M) USB UHCI Controller #2 (rev 02) (prog-if 00 [UHCI])
bf40-bf5f	uhci_hcd


```

00100000-3fec8fff System RAM
01000000-016627f1 Kernel code
016627f2-019b81ff Kernel data
01a9b000-01b81fff Kernel bss
3fec9000-3fffffff reserved
3fef0000-3fefffff pnp 00:00
40000000-43ffffff PCI Bus 0000:02
40000000-43ffffff PCI CardBus 0000:03
44000000-440003ff Intel Corporation 82801DB (ICH4) IDE Controller (rev 02) (prog-if 8a [Master
SecP PriP])
48000000-4bffffff PCI CardBus 0000:03
48000000-480fffff Qualcomm Atheros AR5212/AR5213 Wireless Network Adapter (rev 01)
48000000-480fffff Support for 5xxx series of Atheros 802.11 wireless LAN cards.
e0000000-e7ffffff Intel Corporation 82845G/GL[Brookdale-G]/GE Chipset Integrated Graphics
Device (rev 03) (prog-if 00 [VGA controller])
e8000000-efffffff Intel Corporation 82845G/GL[Brookdale-G]/GE/PE DRAM Controller/Host-Hub
Interface (rev 03)
f6f7f400-f6f7f4ff Intel Corporation 82801DB/DBL/DBM (ICH4/ICH4-L/ICH4-M) AC'97 Audio
Controller (rev 02)
f6f7f400-f6f7f4ff Intel 82801DB-ICH4
f6f7f800-f6f7f9ff Intel Corporation 82801DB/DBL/DBM (ICH4/ICH4-L/ICH4-M) AC'97 Audio
Controller (rev 02)
f6f7f800-f6f7f9ff Intel 82801DB-ICH4
f6f7fc00-f6f7ffff Intel Corporation 82801DB/DBM (ICH4/ICH4-M) USB2 EHCI Controller (rev 02)
(prog-if 20 [EHCI])
f6f7fc00-f6f7ffff ehci_hcd
f6f80000-f6ffffff Intel Corporation 82845G/GL[Brookdale-G]/GE Chipset Integrated Graphics
Device (rev 03) (prog-if 00 [VGA controller])
f8000000-fdffffff PCI Bus 0000:02
f8000000-f800ffff Texas Instruments PCI1510 PC card Cardbus Controller
f8000000-f800ffff yenta_socket
fcffe000-fcffffff Broadcom Corporation BCM4401 100Base-T (rev 01)
fcffe000-fcffffff Broadcom 44xx/47xx 10/100 PCI ethernet driver
feda0000-fedffffff reserved
feda0000-fedffffff pnp 00:00
ffb00000-fffffff reserved
ffb00000-ffbfffff pnp 00:00

```

DMA

```

4          cascade

```

Benchmarks

CPU Blowfish

CPU Blowfish

This Machine	2193 MHz	24.992
Intel(R) Celeron(R) M processor 1.50GHz (null)		26.1876862
PowerPC 740/750 (280.00MHz)	(null)	172.816713

CPU CryptoHash

CPU CryptoHash

This Machine 2193 MHz 34.251

CPU Fibonacci

CPU Fibonacci

This Machine	2193 MHz	6.513
Intel(R) Celeron(R) M processor 1.50GHz (null)		8.1375674
PowerPC 740/750 (280.00MHz)	(null)	58.07682

CPU N-Queens

CPU N-Queens

This Machine 2193 MHz 11.619

FPU FFT

FPU FFT

This Machine 2193 MHz 11.491

FPU Raytracing

FPU Raytracing

This Machine	2193 MHz	27.897
Intel(R) Celeron(R) M processor 1.50GHz (null)		40.8816714
PowerPC 740/750 (280.00MHz)	(null)	161.312647