



ALCON CT-458

High power 45W Long Range 100-200km

Features:

Point to Point or Point to mobile use

High performance

Universal interface on the remote / mobile for fax / data or other telecom equipment use

Economical and easy to use

Excellent signal quality for long range use

RF stability & durability

Scrambler function

20 channels frequency auto scan

Two-way paging & intercom

Modular design

Receiver:

	Mob / Rem Unit	Base Unit
Sensitivity 12dbi Sinad	-125dBm	-125dBm
Frequency Range	382.100MHZ	256.100MHZ
Audio Distortion	<5%	<5%
Image/Harmonic	-70db	-80db
Adjacent Channel Rejection	-70db	-70db
Spurious	-70db	-70db
Power Scuce	AC: 100V / 60Hz AC: 220V / 50Hz Output: DC 13.6V / 16A	

Transmitter

	Mob / Rem Unit	Base Unit
Output power	45 W	45 W
Frequency Range	256.100MHz	382.100MHz
Modulation Type	FM	FM
Spurious Emission	-50db	-60db

NEW
High Speed Data Transmission (14.4K-56K) --
Press Scram. Button to Activate

- No Scram. Indicator Normal(Tel.)
- Scram. Indicator On Scram. On
- Scram. Indicator On Data Trans. (flashing)

Application :
Islands, mines, jungles, mountain, isolated communities, farms, country sides, village areas...

High Speed Data Transmission (14.4k~56k)...

Base Unit

Remote Unit

AT-602 Remote Phone

AT-100 Remote Phone

Modem Unit

PSIN

Extracell line from PSIN (ex: 104.800)

Telephone: via lines PSIN

**Extend the Telecommunication Service
From the Urban PTT To Rural Areas**

Base Unit




Application :
islands, mines, jungles,
mountains,
isolated communities,
farms, villages



Mini PABX
1/4 or 1/6
analog



Mobile Unit



HOME Phone
or Facsimile

HOME Phone
or Facsimile

R&R GROUP INTERNATIONAL
Taipei Taiwan, Hong Kong, Dubai UAE

Shop-WiFi.com
Wireless communication products