

Clearance: .40
 Shim: Y225
 New Shim: Y250

E

Clearance: .45
 Shim: Y215
 New Shim: Y245

Clearance: .28
 Shim: Y250
 New Shim: Y265

I

Clearance: .30
 Shim: Y255
 New Shim: Y270

← FRONT

Clearance: .33
 Shim: Y230
 New Shim: Y245

E

Clearance: .47
 Shim: Y220
 New Shim: Y250

Clearance: .30
 Shim: Y240
 New Shim: Y255

I

Clearance: .21
 Shim: Y245
 New Shim: Y255

MEASURED CLEARANCE	Intake																													
	INSTALLED PAD NUMBER*																													
0.00 ~ 0.05																														
0.06 ~ 0.10																														
0.11 ~ 0.15																														
0.16 ~ 0.20																														
0.21 ~ 0.25																														
0.26 ~ 0.30																														
0.31 ~ 0.35																														
0.36 ~ 0.40																														
0.41 ~ 0.45																														
0.46 ~ 0.50																														
0.51 ~ 0.55																														
0.56 ~ 0.60																														
0.61 ~ 0.65																														
0.66 ~ 0.70																														
0.71 ~ 0.75																														
0.76 ~ 0.80																														
0.81 ~ 0.85																														
0.86 ~ 0.90																														
0.91 ~ 0.95																														
0.96 ~ 1.00																														
1.01 ~ 1.05																														
1.06 ~ 1.10																														
1.11 ~ 1.15																														
1.16 ~ 1.20																														
1.21 ~ 1.25																														
1.26 ~ 1.30																														
1.31 ~ 1.35																														

VALVE CLEARANCE (engine cold)
 0.11 ~ 0.15 mm
 Example: Installed is 250
 Measured clearance is 0.32 mm
 Replace 250 pad with 270
 *Pad number (example):
 Pad No. 250 = 2.50 mm
 Pad No. 255 = 2.55 mm
 Always install pad with number down.

MEASURED CLEARANCE	Exhaust																													
	INSTALLED PAD NUMBER*																													
0.00 ~ 0.05																														
0.06 ~ 0.10																														
0.11 ~ 0.15																														
0.16 ~ 0.20																														
0.21 ~ 0.25																														
0.26 ~ 0.30																														
0.31 ~ 0.35																														
0.36 ~ 0.40																														
0.41 ~ 0.45																														
0.46 ~ 0.50																														
0.51 ~ 0.55																														
0.56 ~ 0.60																														
0.61 ~ 0.65																														
0.66 ~ 0.70																														
0.71 ~ 0.75																														
0.76 ~ 0.80																														
0.81 ~ 0.85																														
0.86 ~ 0.90																														
0.91 ~ 0.95																														
0.96 ~ 1.00																														
1.01 ~ 1.05																														
1.06 ~ 1.10																														
1.11 ~ 1.15																														
1.16 ~ 1.20																														
1.21 ~ 1.25																														
1.26 ~ 1.30																														
1.31 ~ 1.35																														
1.36 ~ 1.40																														

VALVE CLEARANCE (engine cold)
 0.16 ~ 0.20 mm
 Example: Installed is 250
 Measured clearance is 0.32 mm
 Replace 250 pad with 265
 *Pad number (example):
 Pad No. 250 = 2.50 mm
 Pad No. 255 = 2.55 mm
 Always install pad with number down.