

[CMR336NWIFTPZ 720p Outdoor Wireless PTZ IP Camera](#)

Model: CMR336NWIFPTZ Camera

Imaging sensor: 1/3" CMOS progressive scan

Signal system: PAL / NTSC adjustable

Scanning mode: Progressive scanning

Illumination: Color 0.2 lux, black & white 0.02 lux, IR on 0 lux

Lens: Standard with 3 million pixel 6-16mm fixed focus CS lens

Day and night switch: IR-CUT dual optical filters auto switch in day and night

Electronic shutter: Manual / auto (adjustable, 1 / 25 ~ 1 / 4000 seconds)

White balance: Auto / manual

DNR: 3D-DNR

IR source: SMD array light source+ Finland LEDIL light lens

Effective night vision distance: 100 meters (measured value without light condition)

Standard compression

Image compression: H.264

Video bitrate: 128 Kbps -- 8 Mbps; CBR / VBR adjustable

Audio compression: G.711 / G.726

Audio bitrate: 64 Kbps (G.711) / 16 Kbps (G.726)

Image



Max image size: 1296 x 976

Frame rate: 1920 x 1080 @ 30 fps; 1280 x 960 @ 30 fps; 1280 x 720 @ 30 fps; 704 x 576 @ 25 fps; 640 x 360 @ 25 fps; 352 x 88 @ 25 fps

Image adjustment: Through IE can adjust Saturation, brightness, contrast, sharpness

Image mirroring: Horizontal mirroring, vertical mirroring

Scene: Auto, indoor, outdoor

Digital enlarge: Can achieve through NVR, P2P hd monitoring management software

Function

Storage: Support external TF card storage

Interface protocol: ONVIF

Support protocol: TCP / IP, ICMP , HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1 x, QoS, IPv6, Bonjour (SIP, SRTP optional)

Intelligent alarm: Motion detection, shadow alarm, network cable break, IP address conflict, the full of storage card, the wrong of storage card

Audio pickup: Can add internal audio pickup, also support add external audio pickup

POE power supply: Non support

WIFI: Support WIFI function (optional)

Interface

Communication interface: 1pc RJ45 10M/100M Adaptive Ethernet ports

Basic parameter

Power input: DC 12V \pm 10%

Power consumption: 1W (IR off) / 9.5W (IR on) 1.1W / 9.6W (IR on)

Work environment: humidity is less than 95% (no condensation)

Size: 155 mm x 95 mm x 75 mm