

Technical Data Sheet

MILES ALL SPEC 10W, 30W, 40W

HEAVY DUTY MOTOR OIL

MILES ALL SPEC OILS are high quality low ash engine oils formulated for diesel engines where ash deposits are a problem. The low ash content reduces ash deposits and helps keep intakes clear. MILES ALL SPEC oils are API licensed and exceed API CF-2 and CF requirements. They are recommended for applications requiring MIL-L-2104E and former API categories CE, CD-II and CD. Advantage Monograde 30 and 40 also meet the requirements of former API category SJ, and 10 meets Allison C-4 and CAT TO-2.

Features and Benefits

- Promotes long engine life
- Excellent Protect against rust and corrosion
- Excellent resistance to excessive viscosity increase

Recommended for Applications

MILES ALL SPEC OILS are high quality detergent motor oils recommended for diesel and gasoline engines.

- API CE, CD-II, CD
- API CF-2, SJ
- API CF

Technical Data Sheet

Typical Properties

SAE Grade	10W	30W	40W
CCS, cP(@ -20°C)	1600	-	-
Viscosity, cSt @ 100°C	6.4	11.5	15
Viscosity, cSt @ 40°C	36.5	93.0	143.0
Viscosity Index	125	110	107
Pour Point, °F	-33	-11	+5
Sulfated Ash, Wt. (%)	0.78	0.78	0.78
Total Base No., (D2896)	7	7	7