Specifications and options.

Engine page	ENGINE		BARRA 190			F-GAS			B/	ARRA 245T			BOS	S 260
Maximum prove (DN) 1908/9250/pm 1508/94570/pm 2548/9250/pm 2548/9250/pm 2568/9250/pm 2568/9250/p					4.01		CT 16				Turbo			
Maximum prower (DN)	9 71	1.02		71 10	1.02		0110		1.02.001		Turbo			
Maximum trougue (DIM)		100		nm	15/		rnm		2451		1.			
Bore stroke 92.3 x 99.3m 92.3 x 99.3 x										-				
Displacement Li	1 ()		-			_				-				
TRAINSISION/RATIOS		7.		11	7.		1111		72.					
Second 1.65		Auto		n				Auto						
2nd	•													
1.00														
Heat														
State St														
Column		0.00				0.00								
Reverse 2.09 3.15 2.09 3.40 2.90 3.40 2.90 3.40 2.90		-	0.7	3										
Fuel tank capacity		2.00	2.1	_		2.00								
Self-adjusting diaphram spring		2.09	3.1	5		2.09		3.40		2.90)		3.40	2.90
Battlery 54Ah			011			001 (\			011				241
Same National Column			81L			YUL (USable	*)			81L			}	31L
Alternator			EAAL			EAAL				EAAL			-	1 A b
Clutch type Self-adjusting diaphram spring Z54mm	,													
Diameter MaxIMUM TOWING CAPACITY2 Marwall MaxIMUM TOWING CAPACITY2 Marwall Maximum Maximu		0 - 1615			0 - 1615				D:					
Manual Automatic : 2300kg.46.4 / 1600kg.8.42.	21	Seir-adju		m spring	Seir-adju		am spring		Diap		3			
Manual			254mm			254mm				26/mm			27	9mm
E-Gas XLS SSB C/C ⁸ SSB								40001 24						
E-Gas XL XLS C/C ⁸ SSB							00001							
XL XLS C/C ⁸ SSB				Tile										
SSB C/C® SOP	E-Gas		201			V(0					\/D.(V-0 / 1	V20
Overall length 5348 5086 5348 5086 5331 5086 5348 5101 5101 5101 Overall width9. 1908 1871 1908 1871 1908 1871 1908 1871 187	EVTEDIOD DIMENSIONS (mm)	C /C8.		D	C /C8.		C D			C /		l cep	ARO TURBO	XK8
Overall width? 1908 1871 1908 1871 1908 1871 1908 1871 1870 3095								,					5101	5101
Wheelbase 3095 3	<u> </u>													
Front track 1553 1547 1574 1574 1574 1574 1574 1574 1574 1574 1574 1574 1574 1574 1574 1574 1575 1775														
Rear track 1547 15														
Front overhang 926 926 926 926 926 926 926 932														
Rear overhang 1327 1065 1327 1065 1327 1065 1327 1065 1327 1074														
Suspension type														
Suspension type 1-tonne 34-tonne 1-tonne 1-ton		1327	100	J.J	1327	10)0J	1327	1003	13	<i>L1</i>	1074	1074	1074
Floor level load length 2209.0 1818.8 2209.0 1818.8 2209.0 1818.8 2209.0 1818.8 2209.0 1818.8 2209.0 1818.8 2209.0 1818.8 2209.0 1818.8 2209.0 1818.8 2209.0 1818.8 2209.0 1818.8 2209.0 1818.8 18		1 toppo	3/ toppo	1 tonno	1 toppo	Cnorto	1 toppo	1 toppo	1 toppo	1 toppo	Cnorto	Cnorto	Sports	Sporto
Belt level load length 2209.0 1848.0 2209.0 1848.0 2209.0 1848.0 2209.0 1848.0 1848.0 1848.0 1848.0 1848.0 Wheelhouse cargo width - 1204.5 - 1204.5 - 1204.5 - 1204.5 - 1154.0 11	1 21													
Wheelhouse cargo width - 1204.5 - 1204.5 - 1204.5 - 1154.0 1394.0	3													
Floor and belt level rear opening width 1804.0 1394.0 1804.0 1394	9	2209.0			2209.0			2209.0						
Liftover height 914.3 745.1 746.1 914.3 663.0 746.1 961.0 794.0 961.0 663.0 663.0 663.0 663.0 663.0 Cargo depth 240.8 410.1 240.8 410.1 240.8 410.1 240.8 410.1 240.8 410.1 410.1 410.1 410.1 410.1 VEHICLE MASSES (kg) Suspension type 1-tonne 3-tonne 1-tonne 1-tonne Sports 1-tonne 1-tonne 1-tonne Sports Sports Sports Sports GVM 2805 2505 2805 2805 2805 2805 2805 2805	9	1004.0			1004.0			1004.0						
Cargo depth 240.8 410.1 240.8 410.1 240.8 410.1 240.8 410.1 240.8 410.1 240.8 410.1 240.8 410.1														
VEHICLE MASSES (kg) J-tonne 34-tonne 1-tonne 1-tonne Sports 1-tonne Sports Sports Sports 2805 <t< td=""><td>- U</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>	- U													
Suspension type 1-tonne		240.8	410).1	240.8	41	0.1	240.8	410.1	240.8	410.1	410.1	410.1	410.1
GVM 2805 2505 2805 2805 2350 2805 2805 2805 2280 285 1830 Payload (maximum) 1260 825 1105 1265 665 1100 1230 1060 1230 725 565 495 450	(3)	1 toppo	3/ toppo	1 tonno	1 toppo	Coonto	1 tonno	1 tonno	1 tonno	1 tonno	Coorto	Cnouto	Coorto	Coonto
Kerb mass 1545 1680 1700 1540 1685 1705 1575 1745 1555 1715 1785 1830 Payload (maximum) 1260 825 1105 1265 665 1100 1230 1060 1230 725 565 495 450 Front axle load (maximum) 1165 1165 1165 1165 1165 1165 1165 1165 1165 1165 1165 1165 1165 1165 1165 1170	1 21													
Payload (maximum) 1260 825 1105 1265 665 1100 1230 1060 1230 725 565 495 450 Front axle load (maximum) 1165														
Front axle load (maximum) 1165														
Rear axle load (maximum) 1700 1380 1700 1700 1240 1700 1700 1700 1170 1170 1170 GCM - manual 1200kg towing - auto 1600kg towing 3885 3585 3885 3430 3885 3885 3885 3885 3885 3360 3360 3360 3360 3360 3320 3720<														
GCM - manual 1200kg towing 3885 3585 3885 3885 3430 3885 3885 3885 3885 3885 3360 3360 3360 3360 - auto 1600kg towing 4245 3945 4245 4245 4245 4245 4245 4245 3720 3720 3720	· · · · · · · · · · · · · · · · · · ·													
- auto 1600kg towing 4245 3945 4245 4245 3790 4245 4245 4245 4245 3720 3720 3720 3720	,													
	9 9													
- auto Z30Ukg towing 4875 4575 4875 4875 4420 4875 4875 4875 4875 4350 - 4350	9 9												3/20	
	- auto 2300kg towing	4875	4575	4875	4875	4420	4875	4875	4875	4875	4350	4350	-	4350

VEHICLE MASS RULES

- A. Kerb mass and payload values are approximate only. Kerb (unladen) mass quoted includes full tank of fuel, all standard equipment (plus air-conditioning where not standard) but excludes occupants or luggage/cargo.

 B. Kerb mass values in table on XL, XLS, RTV and XR6 Ute models are given for Barra 190 engine with standard 5-speed manual
- transmission (XR6T and XR8 Ute with 6-speed manual).
- C. GVM (Gross Vehicle Mass) is defined as the sum of the kerb mass and the payload, and vehicle load must not exceed the relevant
- maximum allowable front and rear axle loads (as measured at the wheel to ground interface)
- D. Payload (maximum) is defined as the maximum combined value for the occupants/cargo/added options/additional structures/ towball download (when towing).
- E. For optional automatic transmission add 20kg to kerb mass and deduct 20kg from payload (maximum).
- F. For optional E-Gas engine, add 50kg to kerb mass and deduct 50kg from payload.
 G. For optional heavy duty suspension add 25kg to kerb mass and deduct 25kg from payload (maximum).
 H. For optional factory aluminium tray add 115kg to kerb mass (for Cab Chassis) and deduct 115kg from payload (maximum).
- GCM quoted = GVM + towing capacity (1200kg for manual/1600kg for auto) towball loading (120kg for manual/160kg for auto).
 For optional 2300kg capacity towing kit (auto only) add 630kg to GCM for auto.

 Maximum axle load, GVM and GCM values remain unchanged with E-Gas option.

DRIVE RATIO		XL		XLS	R	TV	XR6		XR6 Turbo	XR8
	C/C	SSB	C/C	SSB	C/C	SSB	C/C	SSB		
3.23:1 ^{A.}	0	S	S	S	0	0	-	-	-	-
3.46:1 ^{B.}	-	-	-	-	-	-	-	-	-	S
3.45:1 ^{c.}	S	0	0	0	S	S	S	S	-	-
2.73:1 ^{D.}	-	-	-	-	-	-	-	-	0	0
3 73·1E.	_	_	_	_	_	_	_	_	S	_

A. Standard on 3/4-tonne XL Styleside Box and XLS Ute models. Ratio applicable when the 1-tonne option is specified with automatic transmission. **B.** Standard on XR8 Ute (manual transmission only). **C.** Standard on 1-tonne XL C/C (manual transmission only), RTV and XR6 Ute models. Ratio applicable when the 1-tonne option is specified with manual transmission. **D.** Ratio applicable on XR6 Turbo and XR8 Ute when automatic transmission option specified. **E.** Standard on XR6 Turbo Ute manual transmission.

S - Standard. O - Options that can be ordered before a vehicle is manufactured. A - Options that can be added at any time. - - Not available. C/C - Cab Chassis. SSB - Styleside Box.

1. Power and torque figures measured using premium unleaded fuel (95 RON). 2. Figures quoted are for braked trailer. Subject to State and Territory regulations. 3. When fitted with Genuine Ford towbar. 4. Towball download and rear axle limits must not be exceeded. Please refer to your Ford Dealer for advice. 5. When fitted with Genuine Ford heavy duty towbar and load levelling kit. 6. 4-Speed transmission models require auxiliary transmission oil cooler (excluding RTV and vehicles fitted with 1-tonne suspension). 7. Maximum towing capacity of Falcon XR6 Turbo Ute is 1,600kg. 8. Cab Chassis dimensions quoted with optional factory fitted tray. 9. Excludes exterior side mirrors.

FEATURES	ALL)	(L	XLS		RTV		XR6		XR6	
MECHANICAL	MODELS	C/C	SSB	C/C	SSB	C/C	SSB	C/C	SSB	TURBO	XR8
Barra 190 4.0L DOHC DIVCT I6	-	S	S	S	S	S	S	S	S	-	-
5-Speed manual transmission	_	S	S	S	S	S	S	S	S	_	_
4-Speed Sequential Sports Shift auto transmission (incl. adaptive shift)	_	0	0	0	0	0	0	0	0	-	_
4-Speed column auto transmission (incl. adaptive shift)	_	0	0	_	_	0	0	_	_	_	_
E-Gas 4.0L DOHC DIVCT 162.	_	0	0	0	O1.	0	0	O1.	O1.	_	_
4-Speed Sequential Sports Shift auto transmission (incl. adaptive shift)	_	S	S	S	S	S	S	S	S	_	_
4-Speed column auto transmission (incl. adaptive shift)	_	0	0	_	_	0	0	_	_	_	_
Barra 245T 4.0L DOHC DIVCT I6 Turbo	_	_	_	_	_	_	_	_	_	S	_
6-Speed manual transmission	_	_	_	_	_	_	_	_	_	S	_
ZF 6-Speed Sequential Sports Shift auto transmission (incl. adaptive shift)	_	_	_	_	_	_	_	_	_	0	_
Boss 260 5.4L DOHC 4V V8	_	_	_	_	_	_	_	_	_	_	S
6-Speed manual transmission	_	_	_	_	_	_	_	_	_	_	S
ZF 6-Speed Sequential Sports Shift auto transmission (incl. adaptive shift)	_	_	_	_	_	_	_	_	_	_	0
RIDE AND HANDLING											
Fully independent double wishbone front suspension	S			_		_	_				_
Hotchkiss rear suspension	S	_									
3/4-Tonne suspension	_	_	S						_		
1-Tonne suspension		S	0	S	0	S	S	O3.		_	_
Heavy duty 1-tonne suspension4-	_	0	0	0	0	3	3	O3.	_	_	_
	-	U	U	U	S	-	_	S	S	S	S
Sports suspension Vented disc front brakes with twin piston caliper	-	S	S	S		- 0	S	S	S	3	3
· · · · · · · · · · · · · · · · · · ·	-	S	S	S	S S	S S	S	S	S	-	-
Solid disc rear brakes with single piston caliper	-	5	5	5	5	5	5	5	5	-	-
Performance brakes with vented front disc with twin piston caliper	-	-	-	-	-	-	-	-	-	S	S
Performance brakes with solid rear disc with single piston caliper	-	-	-	-	-	-	-	-	-	S	S
Rack and pinion power assisted steering	S	-	-	-	-	-	-	-	-	-	-
Turns (lock-to-lock)	2.8	-	-	-	-	-	-	-	-	-	-
Turning circle (kerb-to-kerb)	11.5	-	-	-	-	-	-	-	-	-	-
16" x 6.5" silver steel wheel (rated 1-tonne) – 215/60 R16 99H tyre	-	-	S	-	-	-	-	-	-	-	-
16" x 6.5" silver steel wheel (rated 1-tonne) – 215/60 R16 C 1-tonne tyre	-	S	-	-	-	-	-	-	-	-	-
16" x 7.0" alloy wheel (rated 1-tonne) - 215/60 R16 C 1-tonne tyre	-	-	-	S	-	-	-	O3.	-	-	-
16" x 7.0" alloy wheel (rated 1-tonne) – 215/55 R16 95W tyre	-	-	-	-	S	-	-	-	-	-	-
16" x 7.0" alloy wheel (rated 1-tonne) - 215/65 R16 C 1-tonne tyre	-	-	-	-	-	O/A	O/A	-	-	-	-
17" x 8.0" alloy wheel – 235/45 R17 93W tyre	-	-	-	-	-	-	-	S	S	S	S
16" x 6.5" silver steel spare wheel (rated 1-tonne)5.	-	S6.	S6.	S6.	S7.	-	-	S8.	S8.	-	-
17" x 7.5" black steel spare wheel6.	-	-	-	-	-	-	-	-	-	S	S
16" x 7.0" silver steel wheel (rated 1-tonne) - 215/65 R16 C 1-tonne tyre	-	-	-	-	-	S	S	-	-	-	-
Limited slip differential (LSD)	-	0	0	0	0	-	-	0	0	S	S
Differential locking system (with remote dash mounted switch)	-	-	-	-	-	S	S	-	-	-	-
EXTERIOR											
Body colour mirrors and body colour body side protection mouldings	-	-	-	S	S	-	-	S	S	S	S
Variable speed intermittent windscreen wipers	S	-	-	-	-	-	-	-	-	-	-
Rear/side demister	S	_	_	_	_	-	-	_	_	-	_
On-glass antenna	S	_	_	_	_	-	_	_	_	_	_
Wiring facility for cargo lamp and high mount stop lamp	S	-	_	_	-	_	-	-	-	-	_
Polyethylene loadbed	_	_	S	_	S	-	S	_	S	S	S
Tonneau cover – black with 2 steel bows 9.	_	_	O/A	_	S	_	O/A	_	S	S	S
Underbody protection shields	_	_	_	_	_	S	S	_	_	_	_
Wheel arch fender flares	-	_	_	_	_	S	S	_	_	_	_
Delete tonneau hooks	_	_	0	_	O10.	_	0	_	O10.	O10.	O 10.
Aluminium tray		0	-	0	_	_	-	O11.	_	_	_
Aluminium tray (with side steps and rear mudflaps)		_	_	_	_	0	_	_	_		_
Rear mudflaps		_	A		A	-	S	_	A	A	A
Partial body styling kit			_	S	S		_			_	_
				3	3	_		S	S	S	S
Full body styling kit											

	ALL XL		XLS		RTV		XR6		XR6		
INTERIOR	MODELS	C/C	SSB	C/C	SSB	C/C	SSB	C/C	SSB	TURBO	XR8
Interior Command Centre (ICC) featuring audio and climate LCD screen	S	-	-	-	-	-	-	-	-	-	-
Carpet floor covering	_	0	0	S	S	0	0	S	S	S	S
Rubber floor covering	-	S	S	-	-	S	S	-	-	-	_
Adjustable rake and reach steering column (floor shift only)	S	_	_	_	_	_	_	_	_	_	_
Leather wrapped steering wheel	_	_	_	S	S	_	_	S	S	S	S
Sports leather steering wheel	_	_	_	_	_	_	_	0	0	0	0
Alloy pedal covers	_	Α	Α	Α	Α	Α	Α	S	S	S	S
Cruise control with steering wheel mounted controls	S	_	_	_	_	_	_	_	_	_	_
Power side mirrors 12.	S	_	_	_	_	_	_	_	_	_	_
Power windows with engine off time delay	S	_	_	_	_	_	_	_	_	_	_
Automatic headlamps ON/OFF	S	_	_	_	_	_	_	_	_	_	_
Air-conditioning 13.	_	O/A	O/A	O/A	O/A	O/A	O/A	S	S	S	S
Illuminated entry/exit - remote activated	_	-	-	S	S	-	-	S	S	S	S
Key-out courtesy light	S	_		_	_		_	_	_	_	_
Auto-off interior light	S	_	_	_	_	_	_	_	_	_	_
Driver/passenger adjustable reading lamps	S	_									
Sports instrument cluster with blue illumination and unique XR graphics	-							S	S	S	S
Trip computer including trip time, fuel used, average fuel, average speed,	S	-	_		_		_	J	3	3	3
distance-to-empty LCD display including, trip computer, odometer and speed alert indicator							_				
(audible warning)	S	-	-	-	-	-	-	-	-	-	-
INTERIOR STORAGE											
Centre console bin with lid (except with fixed centre seat) 14.	S	-	-	-	-	-	-	-	-	-	-
Cup holders, door bins, ICC storage console	S	-	-	-	-	-	-	-	-	-	-
Lockable glove box	S	-	-	-	-	-	-	-	-	-	-
Driver side coat hook	S	-	-	-	-	-	-	-	-	-	-
SEATING											
Cloth trim bucket seats	-	S	S	-	-	S	S	-	-	-	-
Fixed centre seat with lap/sash seatbelt 15.	-	0	0	-	-	0	0	-	-	-	-
Cloth trim sports bucket seats	-	-	-	S	S	-	-	S	S	S	S
4-Way power adjustment for driver 14-	S	-	-	-	-	-	-	-	-	-	-
Adjustable lumbar support for driver	S	-	-	-	-	-	-	-	-	-	-
Adjustable lumbar support for passenger	-	-	-	S	S	-	-	S	S	S	S
Quick-tilt forward seats	S	-	-	-	-	-	-	-	-	-	_
AUDIO											
100 Watt AM/FM stereo radio with single CD	S	-	-	-	-	-	-	-	-	-	-
100 Watt AM/FM stereo radio with 6-disc in-dash CD (premium) 14,16,17.	0	-	-	-	_	-	-	-	-	-	_
Steering wheel mounted audio controls	S	-	-	-	_	-	-	-	_	-	-
SAFETY AND SECURITY											
Driver airbag	S	-	-	-	-	-	-	-	-	-	-
Passenger airbag	0	_	-	-	_	-	-	_	_	_	_
Adjustable seatbelt height	S	_	_	_	_	_	_	_	_	_	_
Beltminder™ system (light and audible warning – driver only)	S	_	_	_	_	_	_	_	_	_	_
Pyrotechnic seatbelt buckle pretensioner	S	_	_	_	_	_	-	-	_	_	_
Restraints control module, driver seat position sensor, crash severity sensor		_	_	_	_	_	_	_	_	_	_
Child seat anchorage point	S	_	_	_	_	_	_	_	_	_	_
Smartshield security system	S	_	_	_	_	_	_	_	_	_	_
Remote central locking	S	_	_	_	_	_	_	_	_	_	_
Anti-lock Braking System (ABS)	_	0	0	0	0	S	S	S	S	S	S
Traction Control		_	_	_	_	_	_	S18.	S 18.	S	S
ABS and Traction Control safety pack 19.		0	0	0	0		_		5.0.	5	_
ABS and passenger airbag safety pack		0	0	0	0		_				
ABS, passenger airbag salety pack ABS, passenger airbag and Traction Control safety pack 19.		0	0	0	0						
		U	U	U	U						
TOWING 1600kg rated (auto)/1200kg rated (manual) towbar ^{20.}	0										

		EXTERIOR COLOUR AVAILABILITY		
Model	XL	RTV	XLS	XR
Exterior colour				
Ego*	А	Α	А	Α
Winter White	Α	Α	Α	Α
Lightning Strike*	A	A	A	Α
Silhouette*	Α	A	Α	Α
Steel*	A	Α	Α	-
Breeze*	-	-	-	Α
Neo*	-	-	-	Α
Bionic*1.	-	-	-	Α
Silk#	A	A	A	Α
Seduce*	-	-	-	Α
Dash#2-	-	-	-	Α
Octane*	-	-	-	Α
Vixen	A	А	A	A
Flare#3.	Α	А	Α	Α
Conquer#4.	А	A	A	A

A - Available. - - Not available.

1. Bionic ends October, 2007. 2. Dash available November, 2007. 3. Flare ends November, 2007. 4. Conquer ends January, 2008. Ford reserves the right to discontinue or change any of the exterior colours referred to in this brochure at any time without notice. Every effort has been made to depict vehicle colours and trims as realistically as possible in this brochure, however some variation may occur due to printing limitations. See your authorised Ford Dealer to view actual colours.

	EXTE	RIOR/SEAT TRIM C	OMBINATIONS FOR	XR MODELS			
Seat Trim	Silver	Red	Empire Blue	Trans Orange	Citric Acid	Breeze	Leather
Exterior Colour							
Ego	0	0	S	0	0	0	CO
Winter White	0	0	S	0	0	0	CO
Lightning Strike	0	0	S	0	0	0	CO
Silhouette	0	0	S	0	0	0	CO
Breeze	0	-	-	-	-	S	CO
Neo	0	0	S	-	-	-	CO
Bionic 1.	0	0	S	-	-	-	CO
Silk	S	0	0	-	-	-	CO
Seduce	0	S	-	-	-	-	CO
Dash ² ·	S	-	-	-	-	-	CO
Octane	0	0	-	S	-	-	CO
Vixen	0	S	-	-	-	-	CO
Flare ³ .	0	-	-	S	-	-	CO
Conquer4-	0	-	S	-	-	-	CO

S – Standard. **O** – Optional (at no extra cost). **CO** – Cost Option. – – Not available.

1. Bionic ends October, 2007. 2. Dash available November, 2007. 3. Flare ends November, 2007. 4. Conquer ends January, 2008.

EXTER	IOR/SEAT TRIM COME	BINATIONS FOR XR MO	DDELS – XR SPORTS L	EATHER SEAT TRIMS		
Seat Trim	Silver	Red	Empire Blue	Trans Orange	Citric Acid	Breeze
Exterior Colour						
Ego	0	0	S	0	0	0
Winter White	0	0	S	0	0	0
Lightning Strike	0	0	S	0	0	0
Silhouette	0	0	S	0	0	0
Breeze	0	-	-	-	-	S
Neo	0	0	S	-	-	-
Bionic 1.	0	0	S	-	-	-
Silk	S	0	0	-	-	-
Seduce	0	S	-	-	-	-
Dash ² ·	S	-	-	-	-	-
Octane	0	0	-	S	-	-
Vixen	0	S	-	-	-	-
Flare ³ .	0	-	-	S	-	-
Conquer4-	0	-	S	-	-	-

 $[\]textbf{S} - \text{Standard when you order XR sports leather seat trim.} \quad \textbf{O} - \text{Optional.} \quad \textbf{-} - \text{Not available.}$

^{*}Falcon XR8 Ute shown for illustrative purposes. *Falcon XLS Ute shown for illustrative purposes. *Prestige colours are optional extras that incur an additional charge.

^{1.} Bionic ends October, 2007. 2. Dash available November, 2007. 3. Flare ends November, 2007. 4. Conquer ends January, 2008.

OPI	TIONS AND ACCESSORIES AVAILABILITY BY MODEL									
	;	XL	XLS		RTV		XR6		XR6	
EXTERIOR STYLING	C/C	SSB	C/C	SSB	C/C	SSB	C/C	SSB	TURBO	XR8
16 x 7 5 spoke alloy wheels (rated 1-tonne) – tyres ^{1,2} .	O/A	O/A	O/A	O/A	-	-	-	-	-	-
16" x 7 5 spoke sports alloy wheels (rated 1-tonne)3.	Α	А	А	Α	-	-	-	-	-	-
16" x 7 5 spoke RTV alloy wheels (rated 1-tonne) – 215/65 R16C tyres 3.	-	-	-	-	O/A	O/A	-	-	-	-
18" x 8 5 spoke alloy wheels - 245/40 ZR18 sport tyres ² ·	-	-	-	-	-	-	O/A	O/A	O/A	O/A
Power bulge hard tonneau – with spoiler/with alloy sports bar/ with alloy sports bar and spoiler	-	O/A	-	O/A	-	O/A	-	O/A	O/A	O/A
Flat hard tonneau cover	-	А	-	А	-	А	-	Α	Α	Α
Alloy sports bar	-	O/A	-	O/A	-	O/A	-	O/A	O/A	O/A
EXTERIOR PROTECTION										
Bonnet protector/foglamp guards4-/headlamp guards/weathershields	А	А	Α	А	А	А	А	А	А	Α
Lights on feature	А	А	А	А	А	А	А	А	Α	Α
Mudspats 5.	А	Α	А	Α	А	А	А	А	Α	Α
Sump guard6.	А	Α	Α	Α	S	S	А	А	-	_
Soft tonneau cover.	Α	Α	Α	S	-	Α	-	S	S	S
_eathergrain tonneau cover	-	Α	-	Α	-	Α	-	Α	Α	А
NTERIOR STYLING										
KR leather seat trim	-	-	_	_	_	_	0	0	0	0
KR sports leather seat trim	_	_	_	_	_	_	0	0	0	0
KR luxury interior package with Premium ICC, XR sports leather seat trim and premium audio with colour screen and dual-zone climate control ⁸ .	-	-	-	-	-	-	0	0	0	0
Nloy pedal pads	А	А	Α	А	А	А	S	S	S	S
Momo leather steering wheel (available in grey, blue ^{9,} or red ^{9,})	O/A	O/A	O/A	O/A	O/A	O/A	O/A	O/A	O/A	0/4
Momo gear knob10./Sequential Sports Shifter11.	A	A	A	A	A	A	A	A	A	A
Scuff plate inserts	Α	А	Α	Α	Α	А	Α	Α	Α	А
NTERIOR COMFORTS AND STORAGE										
Cabin tidy	A	A	Α	A	A	A	A	А	Α	A
Cargo swing net	Α	А	Α	Α	Α	А	Α	Α	Α	Α
Carpet mats/rubber floor mats	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α
XR carpet mats (available in grey, blue or red)	_	_	_	_	_	_	А	Α	Α	Α
Dashmat	Α	Α	Α	Α	Α	Α	Α	Α	Α	Α
Disabled drivers kit 12. (auto only)	А	А	Α	Α	Α	Α	Α	А	Α	А
Pollen filter	Α	A	Α	Α	Α	Α	Α	Α	Α	A
Smokers pack	A	Α	Α	Α	Α	Α	Α	A	Α	A
KR waterproof seat covers	_	_	_	_	_	_	Α	Α	Α	Α
N CAR ELECTRICAL AND ENTERTAINMENT							7.	7.	7.	7.
Air-conditioning kit	O/A	O/A	O/A	O/A	O/A	O/A	S	S	S	S
Bluetooth® mobile phone kit 13,14.	A	A	A	A	A	A	A	A	A	A
Pod®/MP3 audio input13,15./auxiliary audio plug-in13.	A	A	A	A	A	A	A	A	A	A
Fridge 'Day Tripper' 15L/fridge power adaptor	A	A	A	A	A	A	A	A	A	A
Mobile phone presenter ¹³ .	A	A	A	A	A	A	A	A	A	A
SAFETY AND SECURITY	^	^	^	^	^	^	^	^		
Alarm system	A	A	A	A	A	A	A	A	A	A
TOWING AND CARRYING	A	A	A	A	A	A	A	A	A	A
		A		A		٨		۸	٨	۸
Ladder rack 16.	_				_	A	-	A	A	A
Motorcycle tie down kit 17.	_	A	_	A	Α	A	-	A	A	A
Rope rail kit ^{16.} Fowpack – standard 1600kg rated (auto)/1200kg rated (manual) ^{18.}	_	A	_	A	- А	A	_	A	A	A
	Α	Α	Α	Α	Λ	Α	Α	Α	Λ	Α

O - Option that must be ordered before the vehicle is manufactured. A - Accessory that can be added at any time. S - Standard. - - Not available. C/C - Cab Chassis. SSB - Styleside Box.

1. XL.SSB tyres 215/60 R16, XLSSB tyres 225/55 R16. XL/XLS CC 215/60 R16. 2. Set of four. 3. Wheels and tyres sold separately. Fitted in Dealership, not available at time of vehicle manufacture.

4. Available on XR Ute only. 5. Front and rear sets sold separately. Rear sets only available on SSB models.

6. Available only on six cylinder engines with 4-speed transmission. 7. Available of Sets and 58 garder rack, sports bar and factory aluminium tray. 8. Sub-woofer and two-way rear speakers not available on Falcon Ute 9. Momo leather steering wheel is only available in grey at time of manufacture.

10. Manual transmission only. 11. Available on Sequential Sports Shift 4-speed automatic transmission vehicles only. 12. The supplementary kit must be fitted to vehicles with power adjustable pedals. Adjustable pedal functionality (where fitted) is removed when the disabled driver's kit is fitted.

13. Not available for vehicles with a bench seat. 14. Only suitable for Buletoothir's compatible perions. 15. Frond 4-speed automatic transmission models require an auxiliary transmission oil cooler (excluding RTV Ute and vehicles fitted with 1-tonne suspension).